

ULTIME D Patented

Metalfire




Technical Document



ULTIME D MF 1050-75 WHE T

Dimensions (mm)	
- combustion opening WxH:	1086 x 756
- external WxDxH:	1261 x 620 x 2069
- fresh air intake:	2 x Ø150
- flue gas outlet:	Ø250
Technical Data	
- ecolabel:	A
- capacity:	25.2kW
- efficiency:	79%
- CO (volume with 13%O ₂):	0.05%
- dust (volume with 13%O ₂):	30mg/Nm ³
- weight:	400kg
- convection air inlet: min.700cm ² (4 x Ø150)	
- convection air outlet: min.700cm ² (4 x Ø150)	

First aid and technical support:	
- support@metalfire.eu	
- +32 9 261 51 90	
scale 1:20	Rev. B
www.metalfire.eu	EN 13229
General dimensional tolerances up to 6mm Metalfire preserves the right to modify specifications without previous notice	
Sheet 1/3	




Without finishing frame



 Combustible finishing material
 Insulation (thickness see table)

ULTIME D		Patented
Metalfire		
Technical Document		
ULTIME D MF 1050-75 WHE T		
Prescribed insulation thickness (mm)		
Combustible finishing material		
Metalfire recommended SILCA T 300 (TC = 0,09 W/mK)	A = 25mm	
Non-combustible finishing material		
non-combustible materials structural building items EXCLUDED e.g. load bearing walls	A = 0mm	
TC = thermal conductivity		NC = non-combustible
First aid and technical support:		
- support@metalfire.eu		
- +32 9 261 51 90		
scale 1:20		Rev. B
www.metalfire.eu		EN 13229
General dimensional tolerances up to 6mm Metalfire preserves the right to modify specifications without previous notice		Sheet 2/3


With finishing frame 90/10





Min 249 - Max 343
Min 34 - Max 128

Frech air inlet (2xØ150)

1106 (outside)
1086 (inside)



Frech air inlet (2xØ150)

 Combustible finishing material
 Insulation (thickness see table)

ULTIME D Patented

Metalfire

Technical Document

ULTIME D MF 1050-75 WHE T

Prescribed insulation thickness (mm)

Combustable finishing material

Metalfire recommended
SILCA T 300
(TC = 0,09 W/mK)

A = 25mm

Non-combustable finishing material

non-combustable
materials
structural building items
EXCLUDED e.g. load bearing walls

A = 0mm

TC = thermal conductivity

NC = non-combustible

First aid and technical support:

- support@metalfire.eu
- +32 9 261 51 90

scale 1:20

www.metalfire.eu

EN 13229

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice

Rev.
B

CE

Sheet
3/3